

Are Your Critical Messages Secure?

001161011010100101011001



Now They Will Be

Introducing the Unication Elite Secure Pager

- **Secure Messaging**
Encrypted messages cannot be decoded.
- **Message Lock**
Messages are automatically locked and can only be read by entering a password.
- **Narrow Band Auto Migration**
Automatically detects narrow or wide band networks

Unication

Elite Secure+

Protocol	FLEX	
Band Split	VHF	900 MHz
Frequency Range	143-153 MHz	929-932 MHz
	153-163 MHz	
	163-174 MHz	
Baud Rate (bps)	1600/ 3200/ 6400 bps	
Paging Sensitivity	1600: <= 8 u/Vm 3200: 11 u/Vm 6400: 13.5 u/Vm	
Selectivity	>= 55 dB	>= 50 dB
Spurious & Image Rejection	40 dB	
Frequency Stability	+/-15 ppm	+/-3.5 ppm
Channel Spacing	12.5/ 25 KHz	25 KHz
Receiver Type	Synthesized	
Address Capability	16 FLEX Addresses	
Frequency Deviation	+/-4.8 KHz	
Alert Tone SPL	78 dB @ 12 in (2700 1-lz Standard Alert	
Operating Temperature	5 ⁰ to 40 ⁰ C 40 ⁰ to 105 ⁰ F	
Storage Temperature	-40 ⁰ to 85 ⁰ C	
Battery	1.5V Single AAAlkaline Battery	
Battery Life	Auto Baud Detect Collapse=490 days	
Low Battery Alert Level	1.24 Volts (Programmable)	
Weight	87.5g (3.1oz)	
Dimension	81 X 55 X 18.5 mm (3.19 X 2.16 X 0.73 inch)	
UL Rating	Class 1, Division II, Groups	